

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

Data Sheet

Fujitsu ESPRIMO P900 E85+ Desktop PC

The expandable business workhorse

The ESPRIMO P900 E85+ in a new design and with state-of-the-art Intel® technology is the ideal companion for all those challenging business applications. Produced with selected material and equipped with comprehensive powersave options and energy-saving management, the ESPRIMO microtower PC today already meets the environment requirements of tomorrow. With extended system management functions, intelligent hardware design, extensive tests and a lifecycle of up to 18 months, the high performance levels of this PC meet every requirement.

Microtower

Maximum performance and optimal extendability

- Top-quality, high-value microtower, 7 drive bays, 4 PCI/PCI express interfaces

Environmentally conscious product with ENERGY STAR certification

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle

Quiet

Innovative hardware design, optimized cooling concept

- Pleasant working environment due to an extremely quiet system

System management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology (depending on CPU)

Power-saving and intelligent performance

Low power consumption combined with top performance

- State-of-the-art Intel® Core™ processors with Turbo Boost and hyperthreading technology and a power supply with up to 86% efficiency



Components

Processor	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2100 processor (2 Cores / 4 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics 2000)
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Microsoft Office 2010 preloaded. Purchase a Product Key to activate a full Microsoft Office 2010 suite. Limited Windows XP support. Microsoft discontinued Windows XP certification on system level.
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA, 128 GB, 2.5-inch SATA III, 7200 rpm, 1000 GB, 3.5-inch SATA III, 7200 rpm, 500 GB, 3.5-inch SATA III, 7200 rpm, 320 GB, 3.5-inch SATA II, 7200 rpm, 500 GB, 3.5-inch, business critical SATA II, 7200 rpm, 160 GB, 2.5-inch Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300, 512 MB NVIDIA® GeForce® GT 420 NVIDIA® GeForce® 405 display port full height LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DP to DVI-D (single link) Adapter Cable ATI Radeon® HD 5450, 512 MB 2nd NVIDIA® Quadro® NVS 300, 512 MB
Drives (optional)	Blu-ray Disc™ Triple Writer DVD-ROM DVD Super Multi MultiCard Reader 20in1, USB 2.0, 3.5-Inch MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch
Interface add on cards/components (optional)	WLAN III, 802.11g/Draft-n (Windows only) USB 3.0 PCIe x1 Parallel Interface Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1, powered Dual serial card PCIe x1

Base unit	ESPRIMO P900 E85+
Mainboard	
Mainboard type	D3062
Formfactor	µATX
Chipset	Intel® Q67
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI Raid 1/0
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	14
USB 3.0 total	optional
USB front	4
USB rear	8
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	7
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	2
5.25-inch external bays	2

Slots

PCI-Express 2.0 x16	1 x (312 mm) full height
PCI-Express 2.0 x4 (mech. x16)	1 x (312 mm) full height
PCI-Express x1	1 x (312 mm) full height
PCI (32-bit / 33 MHz)	1 x (170 mm) full height

Graphics on board

Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 83% / 86% / 85% 0-Watt mode with hard-off switch
------------------------------	--

Electrical values

Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption 0-Watt mode with hard-off switch
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=0c06ac4b-6c90-4d28-81a0-c3b694da40d5

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

Noise for standard configuration (HDD, ODD, FDD)

Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load (Blue angel requirement)	3.9 B/ 26 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.3 B/ 20 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.4 B/ 21 dB(A)
Noise Operation mode 4: High load Idle mode (Blue Angel requirement)	3.4 B/ 21 dB(A) 3.3 B/ 20 dB(A)
Noise notes / description	A weighted sound power level L _{wad} (in B) / workplace related A-weighted sound pressure level L _{pAm} (in dB(A)), Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	175 x 419 x 395 mm
Operating position	Vertical
Weight	approx. 11 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C

Compliance

Product	ESPRIMO P900
Model	M15W-3062
Germany	Blauer Engel / Blue Angel in progress GS in progress
Europe	CE Nordic Swan
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery)
------------------------------------	---

Additional Software

Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)
---------------------------------------	--

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Thermal management
Extended lifetime

Compatibility (references)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0
SMBIOS

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 7.0
Manageability software	DeskView 10.x client management including:
DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu

Security

System protection	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
Audit proof protection	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

Serviceability

EasyFix
EasyChange for HDD
EasyChange for optical drives

Packaging information

Packaging dimension	516x278x562 mm
Max. quantity / pallet	24

Packaging information

Material - Weight (g) Carton	1405 g
Material - Weight (g) EPS / PS	160 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO P900 E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P900 E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/ESPRIMO>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2011-04-19 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions